

# Nitrile Chemical Glove 33cm

PRODUCT CODE: RNF15



## DESCRIPTION

Flock Lined Nitrile Gloves, 15mil

## FEATURES AND BENEFITS

- Nitrile rubber for solvent resistance
- Maximum rating for abrasion resistance
- Pure cotton flock lining to absorb perspiration and provide added comfort
- Anti-slip pattern for good grip in wet and dry conditions
- Straight cuff
- Chlorine washed
- Materials comply with FDA regulations for food contact
- HACCP Food Safety Approved

## APPLICATIONS

Industrial Cleaning, Petrochemical Industry, Aerospace and Automobile Industry, Printing Industry, Surface Coating, Metal Fabrication, Machining Operations

## PRODUCT DETAILS

- Elastomer : Nitrile rubber
- Thickness : 0.38mm +/- 0.05
- Lining : Flocklined
- Former : Reverse Lozenge, CVIL
- Cuff Type : Straight
- Exterior : Matt finish
- Colours : Green



## CE CERTIFICATION

Conforms to European Council Directive 89/686/EEC relating to (Complex Design) Personal Protective Equipment after assessment against standards EN 374, EN 388, EN 420:2003

See page reverse for details.

## PHYSICAL DIMENSIONS

Size	Dimensions	Wrist	Cuff	Length
6	218	185	284	330
7	214	206	296	330
8	220	218	302	330
9	244	284	424	330
10	268	256	326	330
11	278	268	330	330

Circumference in mm, +/- 5mm

Tolerance +/- 10mm

## PHYSICAL PROPERTIES

Tensile Strength	20.0 MPa (min)	Modulus at 300% Elongation	6 MPa (max)
Elongation at break	400% (min)	Load at break	45.0 N (min)

# Nitrile Chemical Glove 33cm

PRODUCT CODE: RNF15



## CE CERTIFICATION



### Chemical Risks EN 374

Methanol	Level 2
n-Heptane	Level 2
Sodium hydroxide, 40%	Level 3
Acetic acid, glacial	Level 2
Aliphatic petroleum distillates	Level 2
Amyl acetate	Level 6
Amyl alcohol	Level 6
Auto diesel	Level 6
[gas oil - 38sec)	Level 4
Butanol, pure	Level 4
Carbon tetrachloride	Level 6
Cellosolve solvent	Level 6
Cutting oil	Level 5
Cyclohexane	Level 6
Dibutyl phthallate	Level 2
Di-isobutyl ketone	Level 6
Dimethyl sulphoxide	Level 6
Ethyl ether	Level 6
Ethylene glycol	Level 6
Formaldehyde, 37%	Level 2
Hydrochloric acid, 37%	Level 6
Hydrofluoric acid, 48%	Level 6
Hydrogen peroxide, 30%	Level 6
Iso octane	Level 6
Iso-propyl alcohol	Level 6
Kerosene	Level 4
[Burning Oil - 28sec)	Level 5
Methyl cellosolve solvent	Level 2
Methyl t-butyl ether	Level 4
Methylamine	Level 6
Naptha solvent	Level 5
Petroleum ether	Level 6
Sulphuric acid, 50%	Level 1
Unleaded petrol [4 star - 98 octane)	Level 6
Tetrachloro ethylene	Level 6
Toluene	Level 1
Triethanolamine	Abrasion
Turpene (D-Limonene)	Blade
Turpentine	Tear
Xylene	Puncture



### Mechanical Risks EN 388

Abrasion Resistance	Level 4
Blade Cut Resistance	Level 1
Tear Resistance	Level 0
Puncture Resistance	Level 1



### Micro O. Risks EN 374

Air Leak Test	Passed
Water Leak Test	Passed



Conforms to ASTM D4679 of 2002

#### WA

T [618] 9301 7888  
F [618] 9310 7889  
E wa@paramountsafety.com.au

#### MELBOURNE

T [613] 9764 9900  
F [613] 9764 9800  
E vic@paramountsafety.com.au

#### SYDNEY

T [612] 9601 3877  
F [612] 9601 3899  
E nsw@paramountsafety.com.au

#### BRISBANE

T [617] 3806 2699  
F [617] 3806 3266  
E qld@paramountsafety.com.au

#### ADELAIDE

M 0424 504 802  
T [613] 9764 9900  
F [613] 9764 9800  
E sa@paramountsafety.com.au

#### NEW ZEALAND

T [649] 525 8090  
F [649] 523 9773  
E nz@paramountsafety.co.nz