

FEATURES AND BENEFITS

P1 Rating for protection against mechanically generated particles

Provalve for increased exhalation and comfort - reduces heat build up under mask

Latex free dual straps give firm and comfortable fit

Resealable poly bag ensuring masks stays hygienically sealed

APPLICATIONS

These respirators maybe suitable for the following suggested applications (but are not limited to): Class P1:

Sanding, Grinding, Cutting, Drilling, Plastering, Rendering, Excavation, Powders or Dusts

PRODUCT DETAILS

Straps : Latex-free rubber band
 Filter : Polypropylene melt-blown
 Weight : 13.8g±1g each
 Qty/Box : 12 masks
 Qty/Carton : 20 boxes

PRODUCT CODE: PC315



AS/NZS 1716
ID No 5051

STORAGE AND TRANSPORTATION

Shelf life of the unopened product is three (3) years from the date of manufacture when stored within temperature range of -20°C to +25°C and at less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided

WARNINGS AND USE LIMITATIONS

ProChoice Particulate Respirators PC315
 Always ensure the complete product is:

- Suitable for the application;
 - Fitted correctly;
 - Worn during all periods of exposure;
 - Replaced when necessary
-

STANDARDS

AS NZS 1716-2012 Respiratory protective devices: P2 rating. To be used in conjunction with:
 AS NZS 1715-2009 Selection use and maintenance of respiratory protective equipment



WA

T (618) 9301 7888
 F (618) 9310 7889
 E wa@paramountsafety.com.au

MELBOURNE

T (613) 9764 9900
 F (613) 9764 9800
 E vic@paramountsafety.com.au

SYDNEY

T (612) 9601 3877
 F (612) 9601 3899
 E nsw@paramountsafety.com.au

BRISBANE

T (617) 3806 2699
 F (617) 3806 3266
 E qld@paramountsafety.com.au

ADELAIDE

M 0424 504 802
 T (613) 9764 9900
 F (613) 9764 9800
 E sa@paramountsafety.com.au

NEW ZEALAND

T (649) 525 8090
 F (649) 523 9773
 E nz@paramountsafety.co.nz