PROCHOICE P2 DISPOSABLE RESPIRATOR

PRODUCT CODE: PC321





FEATURES AND BENEFITS

P2 Rating for protection against mechanically and thermally generated particles

Latex free dual straps give firm and comfortable fit

Resealable poly bag ensuring masks stay hygenically sealed



APPLICATIONS

These respirators may be suitable for the following suggested applications (but are not limited to): Class P1: Sanding, Grinding, Cutting, Drilling, Sawing, Plastering, Rendering, Excavation, Powders or Dusts

Class P2 (as for P1 above, plus): Light Welding, Soldering, Foundry Operations, Aerosols, Diesel Particulate Materials



PRODUCT CODE: PC321





Straps Latex-free rubber band Filter Polypropylene melt-blown

Weight 14.2 ± 1 g each Qty/Box 12 masks Qty/Carton : 20 boxes



STORAGE AND TRANSPORTATION

Shelf life of the unopened product is three (3) years from the date of manufacture when stored within temperature range of -20°C to +25°C and at less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided



WARNINGS AND USE LIMITATIONS

ProChoice Particulate Respirator PC321 Always ensure the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure
- Replaced when necessary



STANDARDS

AS NZS 1716-2012 Respiratory protective devices: P2 rating. To be used in conjunction with: AS NZS 1715-2009 Selection use and maintenance of respiratory protective equipment

T (618) 9301 7888

wa@paramountsafety.com.au

MELBOURNE

SYDNEY

T (612) 9601 3877 F (612) 9601 3899

BRISBANE

T (617) 3806 2699

ADELAIDE M 0424 504 802

T [613] 9764 9900 F [613] 9764 9800

NEW ZEALAND

T (649) 525 8090 F (649) 523 9773 E nz@paramountsafety.co.nz