PROMESH RESPIRATOR P2 WITH VALVE



DESCRIPTION

ProMesh Respirator P2 with Valve



FEATURES AND BENEFITS

Flexible mesh which ensures optimum shape retention for a perfect,

airtight fit during long periods of wear

P2 rating protects against mechanically and thermally generated particles Moulded nose-piece for close fit

Quicklock straps for easy fit and release

Provalve for increased exhalation efficiency and comfort - reduces

heat build up under mask

Resealable poly bag ensuring masks stay hygenically sealed



APPLICATIONS

These respirators maybe suitable for the following suggested applications (but are not limited to):

Class P1:

- Sanding, grinding, cutting, drilling
- Plastering, rendering, excavation
- With powders or dusts

Class P2 (as for P1 above plus):

- Light welding, soldering
- Foundry operations
- Aerosols
- Diesel particulate material



PRODUCT DETAILS

Straps : Textile Elastic/LLDPE

Mask Lining Terylene + PU Outer Mesh : EVA+LDPE

: Polypropylene Melt-Blown Filter

Weight 26.5±2g each Qty/Box : PC822 - 12 masks

Qty/Carton : 20 boxes



STANDARDS

AS NZS 1716-2012 Respiratory protective devices

To be used in conjunction with:

AS NZS 1715-2009 Selection use and maintenance of respiratory protective equipment



STORAGE AND TRANSPORTATION

Shelf life of the unopened product is three (3) years from date of manufacture when stored within temperature range of -20°C to +25°C and at less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.



WARNINGS AND USE LIMITATIONS

ProMesh Respirators PC822:

- Always ensure the complete product is: Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- · Replaced when necessary.



PRODUCT CODE: PC822





M 0424 504 802

T [613] 9764 9900 F [613] 9764 9800 E sa@paramountsafety.com.au