PROPOD DISPOSABLE EARPLUGS

PRODUCT CODE: EPODU | EPODC



FEATURES AND BENEFITS

Class 3, SLC80 18dB Corded version for easy re-fitting and to stop PODS falling to floor Hands free insertion for better hygiene Maneuverable stem design allows clean and precise insertion of plugs High rebound foam for a more secure ear canal fit

PRODUCT DETAILS

Materials of Construction

Colours

Size

Foam: Pu Stem: PVC

Cord: PVC Hi-Vis Orange Foam/Black Stem White Standard One Size EPODU- Qty Box/Carton - 50prs /10 boxes EPODC- Qty Box/Carton - 50prs /10 boxes

STANDARDS

Qty/Carton

AS / NZS1270- SLC80 Class 3 18dB Certified by SAI Global - License number: SMKH25293

ATTENUATION TABLE (ATTENUATION IN DECIBELS)

FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	25.0	23.0	23.0	24.0	30.0	34.0	36.0
STANDARD DEVIATION	12.0	10.0	9.0	10.0	10.0	8.0	10.0
MEAN-MINUS-STANDARD DEVIATION ATTENUATION	13.0	13.0	13.0	14.0	20.0	26.0	26.0

SLC80 Value is 18 (Class 3)

Hearing protector Class 3 tested to AS / NZS1270 When selected, used and maintained as specified in AS / NZS1269. this protector may be used in noise up to 100dB (A) assuming an 85dB (A) criterion. A lower criterion may require a higher protector class.

FITTING INSTRUCTIONS



Using the opposite hand, reach accross your head and pull ear up and back to maximize ear opening



Insert plug gently until you feel it seeling



The tip of the earplug should be visible when viewed in front. Repeat steps 1 & 2 for the other ear

BRISBANE

ADELAIDE

M 0424 504 802 [613] 9764 9900 F [613] 9764 9800

NEW ZEALAND

T (649) 525 8090 F [649] 523 9773 E nz@paramountsafety.co.nz





PRODUCT CODE : EPODC

PRODUCT CODE : EPODU



WΔ

T (618) 9301 7888 F (618) 9310 7889 E wa@paramountsafety.com.au

T [613] 9764 9900 E [613] 9764 9800 E vic@paramountsafety.com.au

T (612) 9601 3877 F (612) 9601 3899 E nsw@paramountsafety.com.au

T (617) 3806 2699 F (617) 3806 3266 E gld@paramountsafety.com.au

E sa@paramountsafety.com.au